



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Frequency Characteristics of Diffuse Scattering in SHF band in Indoor Environments

SAITO, Kentaro ; Hanpinitsak, Panawit ; Fan, Wei; Takada, Junichi; Pedersen, Gert Frølund

Published in:
2019 URSI Asia-Pacific Radio Science Conference (AP-RASC)

DOI (link to publication from Publisher):
[10.23919/URSIAP-RASC.2019.8738192](https://doi.org/10.23919/URSIAP-RASC.2019.8738192)

Publication date:
2019

[Link to publication from Aalborg University](#)

Citation for published version (APA):
SAITO, K., Hanpinitsak, P., Fan, W., Takada, J., & Pedersen, G. F. (2019). Frequency Characteristics of Diffuse Scattering in SHF band in Indoor Environments. In *2019 URSI Asia-Pacific Radio Science Conference (AP-RASC)* [8738192] IEEE. <https://doi.org/10.23919/URSIAP-RASC.2019.8738192>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.



Frequency Characteristics of Diffuse Scattering in SHF band in Indoor Environments

Kentaro Saito ⁽¹⁾, Panawit Hanpinitsak ⁽¹⁾, Wei Fan⁽²⁾, Jun-ichi Takada⁽¹⁾, and Gert F. Pedersen⁽²⁾

(1) School of Environment and Society, Tokyo Institute of Technology, Tokyo, Japan,
email: {saitouken, hanpinitsak.p, takada}@ide.titech.ac.jp

(2) Department of Electronic Systems, Faculty of Engineering and Science,
Aalborg University, Aalborg, Denmark, email: {wfa, gfp}@es.aau.dk

In the fifth-generation mobile communication system (5G), the millimeter wave band wireless communication is highly expected to increase the network capacity drastically. The radio propagation characteristics in the millimeter wave band are thought to be quite different from the microwave band that has been used for the current mobile wireless communication system. Therefore, it is needed to clarify those differences in a comparable way for the feasibility investigation of those high-frequency band systems in the actual environment.

In this paper, we focused on the frequency characteristics of the diffuse scattering of radio waves. The diffuse scattering is caused by the irregular scattering from uneven reflection surfaces, and it is thought to have the significant frequency dependency. However, those characteristics have not been clarified even though it affects the multiple-input multiple-output (MIMO) transmission performance. We conducted the channel measurements in 3 GHz, 10 GHz and 28 GHz bands in several indoor environments to solve the issue. The measurement system was the vector network analyzer (VNA) based channel sounder. And the propagation delay and angle characteristics of radio waves were evaluated by the virtual uniform cylindrical array-based measurement. The result showed that the power and the angular spread of diffuse scattering tended to decrease as the carrier frequency increased. The parameter estimation of diffuse scattering waves from the measured data and the further detailed investigation of the physical mechanism will be the future works.